



MERCURY DISPLACEMENT INDUSTRIES, INC.

Post Office Box 710 - U.S. 12 East - Edwardsburg, Michigan 49112-0710


Phone (269) 663-8574 - Fax (269) 663-2924

(800) 634-4077

35NO-120AHU



INDUSTRIAL CONTROL EQUIPMENT



* CONTACT RESISTANCE .003 ohms

* TEMPERATURE RANGE -35° TO +85° C

* DIELECTRIC WITHSTAND 2,500 VAC RMS

* COIL TERMINALS #6 BINDING HEAD SCREWS TORQUE TO 7 IN-LB

* OPERATE TIME 50 MILLISECONDS

* LOAD TERMINALS 4-14 A.W.G. COMPRESSION TYPE TORQUE TO 31.5 IN-LB

* RELEASE TIME 80 MILLISECONDS

* RATINGS:

* SINGLE POLE / SINGLE THROW

CONTACTS: 35 AMP @ 480 VAC
RESISTIVE OR GEN. PUPOSE

* MAGNETICALLY ACTIVATED

COIL: 120V 50/60 Hz

CURRENT: 53 mA

* MERCURY CONTACTOR

RESISTANCE: 1,250 Ω

VA: 6.4 WATTAGE: 3.5

* LIFE CYCLE ENDURANCE TESTS: U.L. 508 @ 100,00 & CSA 22.2 @ 250,000 CYCLES

Contactors - Relays - Switches

J.J.S. 12-10-2013

<http://www.mdius.com>