



MERCURY DISPLACEMENT INDUSTRIES, INC.

Post Office Box 710 - U.S. 12 East - Edwardsburg, Michigan 49112-0710

Phone (269) 663-8574 - Fax (269) 663-2924

(800) 634-4077

DORC-120A-0.3

NORMALLY CLOSED TIME DELAY RELAY

ACCEPTS 6 TO 14 AWG

LINE

LOAD

.205" DIA.
(2) HOLES

6-32
COIL SCREWS

1 $\frac{3}{16}$ "

1 $\frac{5}{8}$ "

1 $\frac{3}{16}$ "

1 $\frac{13}{16}$ "

3 $\frac{1}{2}$ "

2 $\frac{5}{32}$ "



939S
LISTED

INDUSTRIAL CONTROL
EQUIPMENT



LR 41198
CERTIFIED

- * DIELECTRIC WITHSTAND 2,500 VAC RMS
- * RELEASE TIME 0.3 SECONDS
- * RATINGS:
 - CONTACTS: 10 AMPS @ 120 VAC
 - PILOT DUTY RATING 720 VA
 - COIL: 120V 50/60 Hz
- * TEMPERATURE RANGE -35° TO +85° C
- * COIL TERMINALS #6 BINDING HEAD SCREWS
TORQUE TO 7 IN-LB
- * SINGLE POLE / SINGLE THROW
- * MAGNETICALLY ACTIVATED
- * MERCURY TO MERCURY CONTACTOR

