




# MERCURY DISPLACEMENT INDUSTRIES, INC.

Post Office Box 710 - U.S. 12 East - Edwardsburg, Michigan 49112-0710

Phone (269) 663-8574 - Fax (269) 663-2924

(800) 634-4077

## SP-1136-120A



- \* CONTACT RESISTANCE .001 ohms
- \* DIELECTRIC WITHSTAND 8,000 VAC RMS
- \* OPERATE TIME 45 MILLISECONDS
- \* RELEASE TIME 60 MILLISECONDS
- \* RATINGS:

CONTACTS: 15 AMPS @ 3500 VAC

COIL: 120 V 60 HZ    CURRENT: 125 mA

RESISTANCE: 380  $\Omega$     VA: 15.0

WATTAGE: 5.9    RESISTIVE OR GENERAL PURPOSE

- \* TEMPERATURE RANGE -35° TO +85° C
- \* COIL TERMINALS #6 BINDING HEAD SCREWS  
TORQUE TO 7 IN-LB
- \* LOAD TERMINALS 2-8 A.W.G. COMPRESSION  
TYPE TORQUE TO 45 IN-LB
- \* SINGLE POLE / SINGLE THROW
- \* MAGNETICALLY ACTIVATED
- \* MERCURY CONTACTOR

Contactors - Relays - Switches

<http://www.mdious.com>